

CHEMICLEAN PRODUCTS

TECHNICAL INFORMATION SHEET

LYNX

High Active Inhibited Acid Cleaner

LYNX is a blend of inorganic acids and special surface active agents, coupled with a unique acid inhibitor. This combination makes **LYNX** an extremely effective cleaner for the removal of cement, mortar stains, lime scale deposits, efflorescence and for the de-rusting of steel surfaces

Features

Powerful

Benefits

LYNX quickly removes even heavy deposits of rust and scale

Versatile

Widely used in the construction industry, **LYNX** de-scales and de-rusts, and can also be used for removing concrete deposits, lime scale and efflorescence, and for etching new concrete prior to sealing. Fully Inhibited The inhibitor system in **LYNX** protects the metal from acid attack, without affecting its cleaning power

Biodegradable

LYNX is fully biodegradable in both hard and soft water areas

Economical

LYNX can be diluted with up to 5 parts water, depending on the degree of soiling

Continued Next Page.....

LYNX

High Active Inhibited Acid Cleaner

Directions for Use

Cement and Mortar Removal: Brush or scrape off heavy deposits before applying **LYNX** by brush or mop. Allow a few minutes contact time before brushing or scrubbing the surface and then rinse off with clean water

Brick Efflorescence: Dilute **LYNX** with 2-3 parts of water in a plastic or rubber bucket. Apply by brush or mop and then rinse off well with clean water (Efflorescence stains may return if the cause is not treated)

Lime and Scale Deposits: **LYNX** can be diluted with up to 5 parts of water, depending upon the degree of scaling. Spray, brush or mop the **LYNX** solution onto the surface to be cleaned. Alternatively, the **LYNX** solution can be circulated over the soiled surface until the scale has been removed. After removal of scale, thoroughly rinse or hose the surface with water

Rust Removal: **LYNX** will quickly remove rust from steel surfaces. Simply apply **LYNX** to the surface or soak the metal parts in the solution until the rust is removed and then rinse well with water. Treated surfaces should be protected, to guard against re-rusting

Concrete Etching: **LYNX** can be diluted with up to 5 parts of water and applied to concrete surfaces. After etching and cleaning processes are completed, thoroughly wash the surface with water before allowing to dry.

PO BOX 2487
HOCKLEY
BIRMINGHAM, B18 5JN
Telephone: 0121-523 8833
Fax: 0121-554 1137
Email: sales@chemiclean.co.uk
Website: www.chemiclean.co.uk



British Institute of
Cleaning Science

Quality and Service with a Smile!!!